

Thinking...

All-in-One Thermal Inkjet Printer



CSPL 127 C



Simple & Flexible




Easy & Clean Operation



Hi-Res & Versatile Coding



Low-Cost & Zero Maintenance



PRINTER SYSTEM

Display	4.3" HD Touch Screen
Operation System	LINUX System
System Language	English/German/Frech/Italian/Spanish/Portuguess/Slovenian/Serbo-Croatian/Czech Bulgarian/Romanian/Polish/Greek/Hungarian/Russian/Ikrainian/Slovak Arabic/Persian/Turkish Chinese/Tradition-Chinese/Japaness/Korean/Hindi/Thai/Vietnamese/Indonesian/Burmese (Available language very for different regions)
Embedded Memory	128MB
Status Alarm	Green: Ready Blue: Printing Red: Alarm
Working Environment	Storage 0 C - 45 C / Working: 5 C - 35 C / Humidity: 10%-80%
Application Mode	INLINE
Electric Power	DC 24V/2A Power Supply
I/O Ports	USB-A, USB-C, Photoelectric-Sensor, Encoder
External Power Adapter	IN: 100-240V / OUT: DV24V 2A
Accessories	Standard: USB*1, Power adapter*1, Encoder *1

PRINTING FEATURES

Resolution	4.3"HD Screen	
Gray Scale	1-10	
Message Components	Text, Numbers, Images, Logo, Barcodes, Dates, Counter, Database etc.	
Image Format	JPG, PNG	
1D Codes	Codes128, Code39, EAN8, EAN13, UPCA, ITF(2of5)	
2D Codes	QR, Data Matrix, GS1DM	
Fonts	True type fonts, Dot-matrix fonts*1	
Printable Materials	Water based ink for porous and semi porous substrates: Paper/Corrugates box/wooden/ Fiberboard/Cotton and etc. Solvent based ink for semi porous and non porous substrates: Plastic/Glass/Metal plates/ Alu-foils/Cables, and etc.	
Ink Throw Distance	1mm-5mm (Distance between nozzle plate and print object)	
Ink Cartridge	Water-based, Color options: Black, Cyan, Magenta, Yellow Solvent based, Color options: Black, Cyan, Magenta, Yellow, White, Green	
Print Height	2.5 mm-12.7 mm (1-5 Lines)	2.5 mm-25.4 mm (1-10 Lines)
Resolution	600 / 300 / 150 DPI	300 / 150 DPI
Max Print Size	12.7 mm* 408 mm	25.4mm* 408 mm
Max Print Speed	60m / min	30m / min

PRINTING MODELS

Model Name	CSPL 127 C
Printhead	Half-inch / One-inch
Power Ports	DC 24V / 2A
I/O Interface	USB, Sensor port
Dimension	105*160*62 mm
Packaging	365*267*135 mm

CONDOT[®]
SYSTEMS PVT. LTD.

Head Office

Condot House, Plot No. F-15, Road No. 23, MIDC, Marol, Opp. Seepz Gate No.1, Andheri (E), Mumbai - 400093. India

Phone : +91-22-6932 7000

Delhi : +91-120-4295256 / 4295257

Email : cspl@condotsystems.com

Web : www.condotsystems.com

Scan to know more

